



aerotech

Size 24


Outlet Area 7.592 Sq.Ft.

Aireng Company
certifies that the ATIL
In Line fan shown
herein is licensed to
bear the **AMCA Seal**.
The ratings shown are
based on tests and
procedures performed in
accordance with **AMCA**
Publication 211 and 311
and comply with the
requirements of the
AMCA Certified Ratings
Program.



Centrifugal In Line

ATIL



Performance certified for installation type A - Free inlet, Free outlet. Power rating bhp does not include transmission losses.
Performance ratings do not include the effects of appurtenances (accessories).

Sound Power Levels

N RPM	Ps in.Wg	Lwo (dB) at Center Frequency (Hz)								LwA
		63	125	250	500	1K	2K	4K	8K	
800	0.62	79	76	73	75	76	70	65	60	79
	1.01	79	75	73	74	75	69	65	61	78
	1.14	82	80	75	75	75	69	64	59	78
850	0.70	81	77	74	76	78	72	67	62	80
	1.14	81	76	74	75	77	71	67	63	80
	1.29	84	81	77	76	77	71	66	61	80
920	0.82	83	79	76	77	80	74	69	64	83
	1.34	83	78	76	76	79	73	69	65	82
	1.51	86	83	79	77	79	73	68	63	82
1000	0.97	86	81	78	79	83	77	72	67	85
	1.58	86	80	78	78	82	76	72	68	84
	1.78	89	85	81	79	82	76	71	66	84
1100	1.17	88	83	83	81	84	79	74	69	87
	1.91	88	82	82	80	83	78	74	70	86
	2.15	91	87	87	81	83	78	73	68	87
1200	1.39	90	86	85	82	85	82	77	72	89
	2.28	90	85	84	82	84	81	77	73	88
	2.56	93	90	89	83	85	81	76	71	89
1300	1.63	92	88	86	84	87	85	79	74	91
	2.67	92	88	85	83	86	84	79	75	90
	3.01	95	92	90	85	86	84	78	73	91
1400	1.90	93	90	88	85	88	87	81	76	92
	3.10	93	90	87	85	87	86	81	77	92
	3.49	97	94	92	87	87	86	80	75	92
1460	2.06	94	92	89	86	89	88	83	78	93
	3.37	94	91	88	86	88	87	82	78	93
	3.79	98	95	93	88	88	87	82	77	93

Values shown are for outlet Lwo and outlet Lwo(A) sound power levels for installation Type A: Free inlet, Free outlet.
The sound power level ratings shown are in decibels, referred to 10⁻¹² watts, calculated per AMCA International Standard 301.
The A-weighted sound ratings shown have been calculated per AMCA International Standard 301.